#### WS-C3750-48TS-S Datasheet

Get a Quote



#### Overview

Cisco Catalyst 3750-48TS switches are an innovative product line that improves LAN operating efficiency by combining industry-leading ease of use and the highest resiliency available for stackable switches. This new product series represents the next generation in desktop switches, and features Cisco StackWise technology, a 32-Gbps stack interconnect that allows customers to build a unified, highly resilient switching system - one switch at a time.For mid-sized organizations and enterprise branch offices, the Cisco Catalyst 3750 Series eases deployment of converged applications and adapts to changing business needs by providing configuration flexibility, support for converged network patterns, and automation of intelligent network-services configurations

- 48 Ethernet 10/100 ports
- 4 SFP-based Gigabit Ethernet ports
- 32-Gbps, high-speed stacking bus
- Innovative stacking technology
- 1 RU stackable, multilayer switch
- Enterprise-class intelligent services delivered to the network edge
- IP Base software feature set (IPB)

# Specification

WS-C3750-48TS-S data sheet		
Manufacturer	Cisco Systems, Inc	
Manufacturer Part Number	WS-C3750-48TS-S	
Product Type	Managed, Stackable 48 ports L3 Switch	
Form Factor	Fixed, Rack Mountable 1U, Stackable/Clustering	
Switch Port density - Uplinks	48 x 10/100 + 4 x SFP	
MAC Address Table Size	12K entries	
Max Number of Stacks	9	
Routing Protocol	RIP-1, RIP-2, EIGRP, static IP routing, RIPng	
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, SSH	
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+	
Features	Flow control, full duplex capability, Layer 3 switching, auto-sensing per device, IP-routing, DHCP support, auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, traffic shaping, stackable, IPv6 support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS)	
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s	
DRAM Memory	128 MB	
Flash Memory	16 MB Flash	

LED Status Lights Indicators	Port status, link activity, port transmission speed, port duplex mode, status		
Connectivity / Expansion Slots			
Interfaces	48 x 10Base-T/100Base-TX - RJ-45 1 x console - RJ-45 - management Network stack device : 4 x SFP (mini-GBIC)		
Power Supply	Power Supply Specifications		
Power Device	Power supply - internal		
Voltage Required	AC 120/230 V ( 50/60 Hz )		
Power Consumption Operational	75 Watt		
Features	Redundant Power System (RPS) connector		
Dimensions / V	Dimensions / Weight / Miscellaneous		
Width	44.5 cm		
Depth	30 cm		
Height	4.4 cm		
Weight	4.1 kg		
Rack Mounting Kit	Optional		
MTBF	217,824 hour(s)		
Compliant Standards	CE, FCC Class A certified, TUV GS, BSMI CNS 13438 Class A, CISPR 24, cUL, EN 60950, EN55022, NOM, VCCI Class A ITE, IEC 60950, EN55024, UL 60950 Third Edition, CISPR 22, CSA 22.2 No. 60950, CB, FCC Part 15, MIC, AS/NZS 3548		
System Software			
Software Included	Cisco IOS IP Base		
Manufacturer V	Manufacturer Warranty		
Service & Support	Limited lifetime warranty		
Service & Support Details	Limited warranty - lifetime		

### Want to Buy

Order Now

Get a Quote

## Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of Cisco, Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.











\$20,000,000 Inventory Available 50%-98% Off Global List Price

### Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com