

# WS-C3750G-48TS-S Datasheet



Get a Quote

## Overview

Cisco Catalyst 3750G-48TS ethernet switch is an innovative switch that improves LAN operating efficiency by combining industry-leading ease of use and the highest resiliency available for stackable switches. This product series represents the next generation in desktop switches, and features Cisco StackWise technology, a 32-Gbps stack interconnect that allows customers to build a unified, highly resilient switching system one switch at a time

- 48 Ethernet 10/100/1000 ports
- 4 SFP-based Gigabit Ethernet ports
- 32-Gbps, high-speed stacking bus
- Innovative stacking technology
- 1 RU stackable, multilayer switch
- Enterprise-class intelligent services delivered to the network edge
- IP Base software feature set (IPB)

## Specification

WS-C3750G-48TS-S data sheet	
<b>Manufacturer</b>	Cisco Systems, Inc
<b>Manufacturer Part Number</b>	WS-C3750G-48TS-S
<b>Product Type</b>	Managed, Stackable 48 ports L3 Switch
<b>Form Factor</b>	Fixed, Rack Mountable 1U, Stackable/Clustering
<b>Switch Port density - Uplinks</b>	48 x 10/100/1000 Ethernet Ports + 4 x SFP
<b>Performance</b>	Switching capacity : 32 Gbps Forwarding performance : 38.7 mpps
<b>MAC Address Table Size</b>	12K entries
<b>Jumbo Frame Support</b>	Yes
<b>Max Number of Stacks</b>	9
<b>Routing Protocol</b>	RIP-1, RIP-2, HSRP, static IP routing, RIPng
<b>Remote Management Protocol</b>	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, SSH, CLI
<b>Authentication Method</b>	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
<b>Features</b>	Flow control, full duplex capability, Layer 3 switching, auto-sensing per device, IP-routing, DHCP support, auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, traffic shaping, stackable, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, Dynamic Trunking Protocol (DTP) support, Port Aggregation Protocol (PAgP) support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS), RADIUS support, Jumbo Frames support, Cisco StackWise Technology, Cisco EnergyWise technology, Uni-Directional Link Detection (UDLD), Rapid Per-VLAN Spanning Tree Plus (PVRST+), Link Aggregation Control Protocol (LACP), Remote Switch Port Analyzer (RSPAN)
<b>Compliant Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s

<b>DRAM Memory</b>	128 MB
<b>Flash Memory</b>	32 MB Flash
<b>LED Status Lights Indicators</b>	Link activity, port transmission speed, port duplex mode, bandwidth utilization %, system, RPS (Redundant Power Supply)
<b>Connectivity / Expansion Slots</b>	
<b>Interfaces</b>	48 x 10Base-T/100Base-TX/1000Base-T - RJ-45 1 x console - RJ-45 - management Network stack device : 1 x x 2 4 x SFP (mini-GBIC)
<b>Power Supply Specifications</b>	
<b>Power Device</b>	Power supply - internal
<b>Voltage Required</b>	AC 120/230 V ( 50/60 Hz )
<b>Power Consumption Operational</b>	160 Watt
<b>Features</b>	Redundant Power System (RPS) connector
<b>Dimensions / Weight / Miscellaneous</b>	
<b>Width</b>	44.5 cm
<b>Depth</b>	40.9 cm
<b>Height</b>	4.4 cm
<b>Weight</b>	6.4 kg
<b>MTBF</b>	165,243 hour(s)
<b>Compliant Standards</b>	CE, FCC Class A certified, TUV GS, BSMI CNS 13438 Class A, CISPR 24, cUL, EN 60950, EN55022, NOM, VCCI Class A ITE, IEC 60950, EN55024, UL 60950 Third Edition, CISPR 22, CSA 22.2 No. 60950, CB, FCC Part 15, MIC, AS/NZS 3548
<b>System Software</b>	
<b>Software Included</b>	Cisco IOS IP Base
<b>Manufacturer Warranty</b>	
<b>Service &amp; Support</b>	Limited lifetime warranty
<b>Service &amp; Support Details</b>	Limited warranty - lifetime

## Want to Buy

[Order Now](#)
[Get a Quote](#)

## Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.





200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

---

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com)